



Electric Heated Hose

Configurator & ordering information



AFS
APPLICATION FAST SET

PROVEN QUALITY. LEADING TECHNOLOGY.

Electric Heated Hose

Graco's Electric Heated hoses are designed for protective coatings that require plural component equipment, such as a Graco XP or XM sprayer. Select the Electric Heated hose that best suits your application's needs.



Configurator

1st and 2nd Digit		3rd Digit		4th Digit		5th Digit		6th Digit		7th Digit	
HH		7		—		—		—		—	
Heated Hose	Pressure Rating 500 bar (7250 PSI)		A Diameter		B Diameter		Additional B Hose	Recirculation Lines		Length	
		5	1/2 inch	5	1/2 inch	1	None	None	5	15 m (50 ft)	
		3	3/8 inch	3	3/8 inch	2	None	x	X	30 m (100 ft)	
				2	1/4 inch	3	1/4 inch	None	Y	45 m (150 ft)	
						4	1/4 inch	x	Z	60 m (200 ft)	

Not all possible combinations are available for sale.

Second B hose is only possible with the 1/2" A-hose and the first B-hose being 3/8".

4th & 5th Digits – Chemical Mix Ratio guidance

Chemical Mix Ratio	"A" & "B" Hose Diameters	Hose Volume Ratio	Hose Part Number
1:1	1/2 x 1/2 inch	1.00:1	HH755_ _
	3/8 x 3/8 inch		HH733_ _
2:1	1/2 x 3/8 inch	1.78:1	HH753_ _
3:1	3/8 x 1/4 inch	2.25:1	HH732_ _
4:1	1/2 x 1/4 inch	4.00:1	HH752_ _

6th Digit – Additional "B" Hose and Recirculation Lines

Add additional "B" hose (1/4 in) and/or recirculation lines to your hose bundle. For example, if you've selected HH7534_ , your bundle would have 1/2 x 3/8 x 1/4 inch A/B/B hose diameters - AND - integrated A/B recirculation lines. The additional B hose provides the ability to better balance viscosities of multiple chemical mix ratios. The integrated recirculation lines provide faster start-up without disconnecting A/B lines from the remote mix manifold.

7th Digit – Hose Length

How far from the machine do you want to locate your remote mix manifold? Select desired hose length to get you there.

Ordering Information – Accessories

- 18C175** Kit, Stand-alone Controller, Electric Heated Hose (240V) Kit contains 240V controller, hose junction box and temperature sensor. Use to add electric heated hose to legacy XM or XP systems. Not for use in hazardous locations.
- 420033** Kit, XP Remote Recirculation (no recirculation hoses) - Includes valves and fittings to easily transition between spray and recirculation without the mess.
- 273185** Kit, XM Remote Recirculation (no recirculation hoses) - Includes valves and fittings to easily transition between spray and recirculation without the mess.



About Graco

Founded in 1926, Graco is a world leader in fluid handling systems and components. Graco products move, measure, control, dispense and apply a wide range of fluids and viscous materials used in vehicle lubrication, commercial and industrial settings.

The company's success is based on its unwavering commitment to technical excellence, world-class manufacturing and unparalleled customer service. Working closely with qualified distributors, Graco offers systems, products and technology that set the quality standard in a wide range of fluid handling solutions. Graco provides equipment for spray finishing, protective coating, paint circulation, lubrication, and dispensing sealants and adhesives, along with power application equipment for the contractor industry. Graco's ongoing investment in fluid management and control will continue to provide innovative solutions to a diverse global market.

GRACO LOCATIONS

MAILING ADDRESS

P.O. Box 1441
Minneapolis, MN 55440-1441
Tel: 612-623-6000
Fax: 612-623-6777

AMERICAS

MINNESOTA
Worldwide Headquarters
Graco Inc.
88-11th Avenue N.E.
Minneapolis, MN 55413

EUROPE

BELGIUM
European Headquarters
Graco Distribution BV
Industrieterrein-Oude Bunders
Slakweidestraat 31
3630 Maasmechelen, Belgium
Tel: 32 89 770 700
Fax: 32 89 770 777

ASIA PACIFIC

AUSTRALIA
Graco Australia Pty Ltd.
Suite 17, 2 Enterprise Drive
Bundoora, Victoria 3083
Australia
Tel: 61 3 9468 8500
Fax: 61 3 9468 8599

CHINA
Graco Fluid Equipment
(Shanghai) Co., Ltd
Building 7, No. 1-2, Wenshui
Road 299
Jing'an District
Shanghai 200436
P.R. China
Tel: 86 512 6260 5711
Fax: 86 21 6495 0077

INDIA

Graco Hong Kong Ltd. India Liaison
Office
Room 432, Augusta Point Regus
Business Centre 53 Golf Course Road
Gurgaon, Haryana India 122001 Tel:
91 124 435 4208
Fax: 91 124 435 4001

JAPAN
Graco K.K.
1-27-12 Hayabuchi
Tsuzuki-ku
Yokohama City, Japan 2240025
Tel: 81 45 593 7300
Fax: 81 45 593 7301

KOREA
Graco Korea Inc.
38, Samsung 1-ro 1-gil
Hwaseong-si, Gyeonggi-do,
18449
Republic of Korea
Tel: 82 31 8015 0961
Fax: 82 31 613 9801

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Graco is certified according to ISO 9001.

APPLICATION FAST SET

483 Avenue Lazare Ponticelli
77220 Gretz-Armainvilliers
Tel : 01 64 16 41 63 - Fax : 01 64 16 48 67
contact@afs-bicomposant.fr
www.afs-bicomposant.fr

Europe
+32 89 770 700
FAX +32 89 770 777
WWW.GRACO.COM