



**REACTOR<sup>®</sup> HEATED HOSE**  
Heated Hoses for Reactor Equipment

**AFS**  
APPLICATION FAST SET

## Ordering Information

### Whip Hose

246050	1/4 in x 10 ft Whip Hose with Xtreme-Wrap, 2000 psi (138 Bar)
246055	1/4 in x 10 ft Whip Hose with Xtreme-Wrap, 3500 psi (241 Bar)

### Xtreme Wrap Scuff Guard

24Y549	3/8 in x 50 ft Hose, 2000 psi (138 Bar), ground wire
24Y678	3/8 in x 50 ft Hose, 2000 psi (138 Bar), thermocouple fluid temperature sensor
24Y240	3/8 in x 50 ft Hose, 2000 psi (138 Bar), RTD fluid temperature sensor
24Y679	3/8 in x 50 ft Hose, 3500 psi (241 Bar), thermocouple fluid temperature sensor
24Y241	3/8 in x 50 ft Hose, 3500 psi (241 Bar), RTD fluid temperature sensor

### Blue Mesh Scuff Guard

256549	3/8 in x 50 ft Hose, 2000 psi (138 Bar), ground wire
246678	3/8 in x 50 ft Hose, 2000 psi (138 Bar), thermocouple fluid temperature sensor
24K240	3/8 in x 50 ft Hose, 2000 psi (138 Bar), RTD fluid temperature sensor
246679	3/8 in x 50 ft Hose, 3500 psi (241 Bar), thermocouple fluid temperature sensor
24K241	3/8 in x 50 ft Hose, 3500 psi (241 Bar), RTD fluid temperature sensor

### No Scuff Guard

246075	3/8 in x 50 ft Hose, 2000 psi (138 Bar), ground wire
246046	3/8 in x 50 ft Hose, 2000 psi (138 Bar), thermocouple fluid temperature sensor
24T839	3/8 in x 50 ft Hose, 2000 psi (138 Bar), RTD fluid temperature sensor
249588	3/8 in x 50 ft Hose, 3500 psi (241 Bar), ground wire
246053	3/8 in x 50 ft Hose, 3500 psi (241 Bar), thermocouple fluid temperature sensor
24U743	3/8 in x 50 ft Hose, 3500 psi (241 Bar), RTD fluid temperature sensor

### Accessories

25M493	Xtreme-Wrap for 50 ft hose section
25M494	Xtreme-Wrap for 10 ft hose section
25M495	Joint Protector

Refer to Manual 309572 for a complete list of heat hose assemblies.

## Improved Hose Design

Graco's heated hoses are designed specifically for use with Graco Reactors. Now, the multi-strand copper heating element that greatly increased the quality of the whip hoses is now available on all heated hoses!

- Provides 10-times\* the flex life compared to previous flat copper heating element (\*testing based on 1/4 in 2000 psi heated hose)
- Long-term, even heating without hot spots
- Backwards compatible with existing Reactor heated hoses

## Keep your hose investment safe with the new Xtreme-Wrap™ Scuff Guard and Joint Protectors

Xtreme-Wrap Scuff Guard provides extra protection and prolonged life to your hose. You may choose a hose that is factory installed with Xtreme-Wrap or purchase the kit to retrofit any existing Graco hose.

- Form fitting to the hose, no more baggy excess material
- Made from urethane coated ballistic nylon for puncture and tear resistance, abrasion protection, and oil and water resistance
- Sheds surface moisture and won't absorb water to weigh down the hose bundle; will not freeze solid in cold temperatures
- Hook and Loop enclosure used on the entire length of the hose for easy access to the hoses, fittings, and fluid temperature sensors
- All whip hoses are factory installed with the improved Xtreme-Wrap

## Joint Protectors

Joint Protectors provide additional protection at the most vulnerable section of the hose: the electrical connections, hose fittings, and fluid temperature sensors.

- Hook and loop closure for easy access
- All 50 ft hoses with Xtreme-Wrap will come with one Joint Protector



**Graco Reactor hoses are ETL Certified and carry the ETL Listed Mark**

In order to maintain your Reactor system ETL certification, ETL approved hoses must be used.



## Contact us today!

Call **866-361-5959** to talk with a Graco representative, or visit [www.graco.com](http://www.graco.com) for more information.

