

AFS

APPLICATION FAST SET



GRACO



T3 TRANSFER PUMP

3:1 Transfer Pump for Material Transfer

T3 Transfer Pump Specifications

- Rated for a continuous output of 4.5 gpm (17 lpm). Allowing enough flow to easily keep up with Graco's biggest proportioner, the H-50.
- Rated for a max inlet pressure of 100 psi (6.8 bar, 0.68 MPa). An air regulator is included with every pump.
- The T3 Transfer Pump is an addition to the T1 and T2 Transfer Pump family.

Ordering Information

T3 – Stainless Steel

- 26A304 T3 pump
- 24Z988 T3 pump package includes 2 pumps and fluid supply kit
- 24Z987 T3 pump package includes 2 pumps, fluid supply kit and air hose kit

T3 – Carbon Steel

- 24Z834 T3 pump
- 25D296 T3 pump package includes 2 pumps and fluid supply kit
- 25D295 T3 pump package includes 2 pumps, fluid supply kit and air hose kit

APPLICATION FAST SET

483 Avenue Lazare Ponticelli
77220 Gretz-Armainvilliers
Tel : 01 64 16 41 63 - Fax : 01 64 16 48 67
contact@afs-bicomposant.fr
www.afs-bicomposant.fr

©2018 Graco Inc. ELECTRONIC ONLY 349870 Rev. B 1/18 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.



Transfer Material Efficiently

Transfer Pumps are required to move A and B materials to the Reactor® Spray Systems. The T3 Transfer Pump combines Graco's proven Merkur® air-motor and popular T2 stainless steel lower. The T3 is a 3:1 ratio pump – using less air pressure to provide the same fluid pressure required.

- **Easier to maneuver** - The overall height of the T3 is 3.7 inches shorter above the drum than the T2, making it easier to remove from the drum inside of a spray rig.
- **More quiet** – Studies show the T3 Transfer Pump is about 3x more quiet than the T2 Transfer Pump.
- **Less maintenance** - the Merkur air-motor is based on air pilot valve technology. The air-motor switching is purely pneumatic. This differs from T1 and T2 Transfer Pumps, which use a mechanical reversing mechanism in the air-motor.

Choose the Right Transfer Pump to Meet Your Needs

	Part Number	Ratio	Maximum Output – Continuous	Maximum Input – Air Pressure	Maximum Output – Fluid Pressure	Maximum Ambient Temperature	Maximum Fluid Temperature	Weight	Height	Manual Number	Wetted Materials
T1	256200	2:1	2.5 gpm (9.5 lpm)	180 psi (12 bar, 1.2 MPa)	360 psi (25 bar, 2.5 MPa)	120°F (49°C)	190°F (88°C)	18 lb (8.4 kg)	51.5 in (131 cm)	312766	Stainless Steel
T2	295616	2.25:1	5.0 gpm (19 lpm)	180 psi (12 bar, 1.2 MPa)	405 psi (28 bar, 2.8 MPa)	120°F (49°C)	190°F (88°C)	21 lb (9.5 kg)	54 in (137 cm)	311882	Stainless Steel
T3 SST	26A304	3:1	4.5 gpm (17 lpm)	100 psi (6.8 bar, 0.68 MPa)	315 psi (21.7 bar, 2.17 MPa)	120°F (49°C)	190°F (88°C)	22 lb (10 kg)	50.3 in (128 cm)	3A5180	Stainless Steel
T3 CS	24Z834	3:1	4.5 gpm (17 lpm)	100 psi (6.8 bar, 0.68 MPa)	315 psi (21.7 bar, 2.17 MPa)	120°F (49°C)	190°F (88°C)	22 lb (10 kg)	50.3 in (128 cm)	3A5180	Carbon Steel

Contact us today!
Visit www.graco.com to learn more or have a Graco representative contact you.

